

DUAL COMMERCIAL BARISTA

CBD 1.5



Cafe Barista brewing technology controls the three vital aspects of the coffee brewing recipe: water temperature, water volume, and water contact time - extracting the best cup of coffee possible. Cafe Barista opens up a new world of flavor profile control by allowing you to select two different settings. And you can brew into two different size dispensers and/or two different strengths with the same machine. You control the time, volume and temperature with the touch of a button (no tools needed). Cafe Barista brewers greatly enhance account profitability by allowing two different beverages to be brewed on a single unit while dramatically reducing installation and set up time.



CBD 1.5 PN: 701238
Shown here with (2) Econo 1.5G
sight gauge PN: 111941



Close up of
level indicator

PN: 109376
1.5 Gallon Econo
Thermal Satellite
with level indicator



“Brew 1” and “Brew 2” selectors provide a choice of two adjustable flavor profiles or portion sizes.

Water Volume: May be adjusted thru the digital display: thirty ounces to three gallons.

Digital Display: Counts down the minutes and seconds remaining until the basket has finished draining. Visa-Brew time may be adjusted.

Water Temperature: May be adjusted between 170 and 210 degrees from the front touch pad.

Pre-infusion: Wets the coffee grounds to de-gas fresh roasted coffee in the basket so that the grounds may be evenly saturated during the brew cycle.

Pulse Brewing: Pulses your chosen water temperature onto the coffee bed for ultimate taste profile accuracy.

Service Light: Indicates the appropriate time for scheduled maintenance and accompanies five “Error” messages when operation is interrupted by a fault.

Water Filtering Light: Offers service operators an opportunity to communicate added value to customers by indicating that fresh water is being drawn into the tank through the filtration system.

Filter Monitor: Alerts the customer when it is time to change the water filter.

Audible Signal: Alerts user when the filter basket has finished draining. Your fresh hot coffee is ready!

Coffee Monitor Light: Indicates the freshness of the last beverage brewed.

Cycle Counter: Monitors the number of brew cycles.

Power Conservation: Allows energy saving during idle time.

Brewer Height and Electrical Specifications:
120/240 volt - 1PH - 6000watt - 25 amp - needs 4 wire plug and cord (not provided) & 30 amp service

120/240 volt - 3PH - 10500 watt - 25.3 amps - needs 5 wire plug and cord (not provided) & 30 amp service wire fitting on back of brewer is located 3” from right side of brewer and 14 1/2” from counter top (18” with 4” legs added)

Item #	Model	Physical Dimensions			Ship Wt.	US Electrical			Canada Electrical		
		H	W	D		Volts	Watts	Amps	Volts	Watts	Amps
701238	CBD-1.5	28.8	22	22	78	240	5500	22.9	240	5500	22.9